

1

RG-SCC800	HDMI VGA

 1000Base-T	100Base-TX	10Base-T			
 RG-SCC800: POE	30W	4	60W	POE+/POE	

1.1 RG- SCC800


	RG-SCC800				
CPU	ARM Cortex-M4 120MHz, 150DMIPS				
BOOTROM	/				
Flash Memory	16MB				
SDRAM	/				
	8				
	1 console				
	6	HDMI	3	3	
	2	VGA	1	1	
	6	USB2.0	2	4	
	4		3	1	
	5	RS232	4	RS485	
	6	IO		/	IO
	4		DC12V		
	3		PDU		220V
	2				220V

	POE	<30W
	PoE	PDU <150W
	0°C	40°C
	-40°C	70°C
	10%	90% RH
	0	5000
	5%	90% RH
	/	
× × mm	442x310x65	
kg	5.35	

RG-SCC8000	A
------------	---

RG-SCC800	8	6	HDMI	6	USB2.0	5	RS232	4	RS485	2	VGA	4
	3	220V PDU	2		5	IR						

1-1RG-SCC800



1-2 RG-SCC800

1.						14.			
2. PDU		/		1		15.			
3. PDU						16. VGA			
4. PDU		/	/	2		17. HDMI	/	2	
5.	1					18. HDMI			
6.	2					19. HDMI	/	1	
7. RS485	/12V					20. VGA	VGA		
8. I/O	/ RS232	/12V				21. HDMI			
9. RS232						22. HDMI			
10. IR						23. HDMI	OPS/		
11. USB2.0	PC/					24.			
12. USB 2.0						25.			
13. Console						26. POE			

RG-SCC800

2

2.1



2.1.1



2.1.2



2.1.3



2.1.4

■

713.26E0F370 /P <</MCID 1>B11C BT/F4 9 44C BT/F5 9 T1 0 0 1 562 9.96 760.08 Tm0.2 q673.54E

2.2.3

$\geq 0.5 \mu m$	/m ³	$\leq 3.5 \times 10^6$
$\geq 5 \mu m$	/m ³	$\leq 3 \times 10^4$

	(mg/m ³)	(mg/m ³)
SO ₂	0.3	1.0
H ₂ S	0.1	0.5
NO ₂		

1Ω

2-1

2.2.6

RG-SCC800



2.2.7 EMI

EMI



■

■

10


■

■

3.3.1

3-1

3-1



4

SwitchSwitch

-5-

B


RG-SCC800

■			5	
	7			
■		7		10
■	HDMI	5		10
■				
■			B-1	
B				

-
-

D-2

B-2



-


D-3

B-3



-
-
-

B-4



mm	mm
10	80~150
10~30	150~200
30	200~300